

SiVend HG 20 Trend Instant

General Information



SiVend HG 20 Trend Instant

General Information



Introduction

- 20 large, illuminated decals behind glass
- Full surface glass panel made from safety glass panel
- Closed delivery carousel made from impactresistant plastic
- Drinks dispense area lighting
- Double cup mechanism with a capacity up to 1,170 cups



Overview

Dimensions: 1,831 x 700 x 755 mm (height x width x depth)*

Weight: approx. 210 kg (if fully equipped)

Number of drinks: Up to 180 cups per hour (varies depending on product and setting)

Electrical connection values: 220-230 V, 50/60 Hz, 16 A (optional 10 A)

Output: 3 kW (optional 2.2 kW)
Water connection: 3/8' internal screw thread

Cup dispense mechanism configuration examples

	Mug diameter	Capacity 4 towers	Capacity 5 towers	Total capacity
Α	70 mm	520	650	1/170
	80 mm	-	-	-
В	70 mm	-	650	-
	80 mm	300	-	950

^{*}Deviations in the housing dimensions are possible due to add-on parts and accessories.

SiVend HG 20 Trend Instant

General Information



С	70 mm	520	-	-
	80 mm	-	375	895
D	70 mm	-	-	-
	80 mm	300	375	675

Design variants

Trims

- EB = Stainless steel panel
- RB = RAL operator panel

Housing colors

- Pure white (RAL 9010)
- White aluminum (RAL 9006)
- Deep black (RAL 9005)

Designs

- Design D 'Colored steam' (Standard)
- Design A "Latte Art"
- Design B "Four cups"
- Design C "Red cup"

Optional

■ LED decoration panel

All figures relating to the design variants can be found in the brochure.



Sielaff GmbH & Co. KG Automatenbau Herrieden Münchener Str. 20 91567 Herrieden Germany

Phone: +49 9825 18-0 Telefax: +49 9825 18-311155

info@sielaff.de www.sielaff.com See here for our company profile video



