


2T-version

SiLine® Snack and Combi M



2T-version

SiLine® Snack and Combi M



Introduction

- 2T-variant: split temperature zones separated by directed air flow, Fresh food / snack
 - Approx. + 10 15 °C on the upper shelves
 - Food-safety storage at ≤ + 4 °C on the lower shelves (LM zone)
- The temperature separation position can be adjusted within a pre-defined range
- The Food safety software monitors the temperature in the LM-zone and ensures that only properly chilled products are dispensed
- Frost monitor



Overview

Dimensions: 1,830* x 990 x 895 mm (height x width x depth)**

Weight: approx. 340 kg (without products, depending on the layout)

Electrical connection values: 220 - 230 V / 50 Hz / min. 10 A

Power consumption: 400 W (varies depending on the type of chiller unit)

Spirals per shelf: 9
Pusher per shelf: 8

Design variants

Design panel

- Design VA = Lower design panel made from Stainless steel
- Design RA = Lower design panel RAL painted

^{* 1,844} mm for Design VA with Design package B

^{**}Deviations in the housing dimensions are possible due to add-on parts and accessories.

2T-version

SiLine® Snack and Combi M



Cabinet colours

- Pure white (RAL 9010)
- White aluminum (RAL 9006)
- Jet black (RAL 9005)

Optional:

The standard design VA can be added with the design package A or B. Design RA can be complemented with Design package A.

Design package A includes:

LED decoration panel

Design package B includes:

- LED-Decoration strips above and below the glass panel
- Upper door decoration panel in stainless steel
- Kickplate in stainless steel

All design variants can be found in the brochure.

Options and accessories

- Lift
- Light barrier



Sielaff GmbH & Co. KG Automatenbau Herrieden Münchener Str. 20 91567 Herrieden Germany

Phone: +49 9825 18-0 Telefax: +49 9825 18-311155

info@sielaff.de www.sielaff.com See here for our company profile video



