

# **LM** version

SiLine® Snack and Combi M



## LM version

## SiLine® Snack and Combi M



#### Introduction

- "Fresh Food" storage ≤ + 4 °C throughout the machine
- The "Food safety software" monitors the temperature in the LM-zone and ensures that only properly chilled products are dispensed.
- Frost monitor
- 6 or 7 product shelves by default
- Capacity: Up to 9 selections per shelf, up to 7 shelves



### Overview

Dimensions: 1,830\* x 990 x 895 mm (height x width x depth)\*\*

Weight: approx. 340 kg (without products, depending on the layout)

Electrical connection values: 220 - 230 V / 50 Hz / min. 10 A

Power consumption: 400 W (varies depending on the type of chiller unit)

Spirals per shelf: 9
Pusher per shelf: 8

### **Design variants**

### Design panel

- Design VA = Lower design panel made from Stainless steel
- Design RA = Lower design panel RAL painted

<sup>\* 1,844</sup> mm for Design VA with Design package B

<sup>\*\*</sup>Deviations in the housing dimensions are possible due to add-on parts and accessories.

# LM version

# SiLine® Snack and Combi M



#### **Cabinet colours**

- Pure white (RAL 9010)
- White aluminum (RAL 9006)
- Jet black (RAL 9005)

### Optional:

The standard design VA can be added with the design package A or B. Design RA can be complemented with Design package A.

### Design package A includes:

LED decoration panel

### Design package B includes:

- LED-Decoration strips above and below the glass panel
- Upper door decoration panel in stainless steel
- Kickplate in stainless steel

All design variants can be found in the brochure.

### **Options and accessories**

- Lift
- Light barrier



Sielaff GmbH & Co. KG Automatenbau Herrieden Münchener Str. 20 91567 Herrieden Germany

Phone: +49 9825 18-0 Telefax: +49 9825 18-311155

info@sielaff.de www.sielaff.com See here for our company profile video



