

LM version

SiLine® Snack and Combi S



LM version

SiLine® Snack and Combi S



Introduction

- "Fresh Food" storage ≤ + 4 °C throughout the machine
- The "Food safety software" monitors the temperature in the LM-zone and ensures that only properly chilled products are dispensed.
- Frost monitor
- 6 or 7 product shelves by default
- Capacity: Up to 9 selections per shelf, up to 7 shelves



Overview

Dimensions: 1,830* x 780 x 895 mm (height x width x depth)**

Weight: approx. 300 kg (without products, depending on the layout)

Electrical connection values: 220 - 230 V / 50 Hz / min. 10 A

Power consumption: 400 W (varies depending on the type of chiller unit)

Spirals per shelf: 6
Pusher per shelf: 6

Design variants

Design panel

- Design VA = Lower design panel made from Stainless steel
- Design RA = Lower design panel RAL painted

^{* 1,844} mm for Design VA with Design package B

^{**}Deviations in the housing dimensions are possible due to add-on parts and accessories.

LM version

SiLine® Snack and Combi S



Cabinet colours

- Pure white (RAL 9010)
- White aluminum (RAL 9006)
- Jet black (RAL 9005)

Optional:

The standard design VA can be added with the design package A or B. Design RA can be complemented with Design package A.

Design package A includes:

LED decoration panel

Design package B includes:

- LED-Decoration strips above and below the glass panel
- Upper door decoration panel in stainless steel
- Kickplate in stainless steel

All design variants can be found in the brochure.

Options and accessories

- Lift
- Light barrier



Sielaff GmbH & Co. KG Automatenbau Herrieden Münchener Str. 20 91567 Herrieden Germany

Phone: +49 9825 18-0 Telefax: +49 9825 18-311155

info@sielaff.de www.sielaff.com See here for our company profile video



