

# SiLine® SiOne S Basic



# SiLine® SiOne S

### **Basic**



#### Introduction

- Reverse vending of disposable and reusable PET bottles, cans and cups with EAN code
- Barcode recognition (up to 20,000 codes)
- Acceptance speed: Up to 30 empties per minute
- © Capacity: Up to 400 bottles (0.5 I PET) or up to 560 cans
- Fits perfectly in a Vending line with other SiLine and vending machines
- Modular design makes it extremely easy to service and recycle



### Overview

Dimensions: 1.830\* x 780 x 716 mm (height x width x depth)\*\*

Weight: Approx. 145 kg

Container size: Max. diameter 140 mm; Max. lenght 380 mm

Acceptance speed: Up to 30 units per minute

Capacity: Approx. 400 bottles (0,5 I PET) or approx. 560 cans

Electrical connection values: 220 - 230 V / 50/60 Hz /mind. 10 A

### **Design variants**

### Design panel

- Design VA = Lower design panel made from Stainless steel
- Design RA = Lower design panel RAL painted

<sup>\*</sup>Design VA with package B is 1,844 mm

<sup>\*\*</sup>Deviations in the housing dimensions are possible due to add-on parts and accessories.

## SiLine® SiOne S Basic



### **Cabinet colours**

■ Jet black (RAL 9005)

### Optional:

The standard design VA can be added with the design package A or B. Design RA can be complemented with Design package A.

### Design package A includes:

LED decoration panel

### Design package B includes:

- LED-Decoration strips above and below the glass panel
- Upper door decoration panel in stainless steel
- Kickplate in stainless steel

All design variants can be found in the brochure.

## **Options and accessories**

- Up to 2 coin hoppers possible
- Sorting into two Sections
- Roller container
- Receipt printer
- Ingress protection, Thread catcher
- Product recognition (cup acceptance is possible either with or without barcodes)



Sielaff GmbH & Co. KG Automatenbau Herrieden Münchener Str. 20 91567 Herrieden Germany

Phone: +49 9825 18-0 Telefax: +49 9825 18-311155

info@sielaff.de www.sielaff.com See here for our company profile video



