

# SiLine® Snack und Combi M RO Basis



# SiLine® Snack und Combi M RO

## **Basis**



#### Introduction

- Protection class: IP24
- Winter resistant up to -20°C
- Rain roof and weatherproof protection
- Impact protection (Standard 12 mm PC)
- Laminated safety glass with UV-light filter (ESG safety glass)
- Reinforced wavy locking lever protection (5 mm stainless steel), the wavy profile prevents prising or lifting
- Coin insert slide and coin return drum
- High security frame with side lock and CES mortice lock (KESO as an option)
- Residual current circuit breaker
- Chiller unit with heater ("Frost monitoring function", which keeps the internal temperature above 0 °C)
- Rear wall (Branding opportunity)



#### Overview

Dimensions: 1,866 x 1,056 x 1,000 mm (height x width x depth)\*

Weight: approx. 440 kg

Electrical connection values: 220 - 230 V / 50 Hz / mind. 10 A

Power consumption: 750 W

\*Deviations in the housing dimensions are possible due to add-on parts and accessories.

# Design variants

### Design panel

- Design VA = Lower design panel made from Stainless
- Design RA = Lower design panel RAL painted

### **Cabinet colours**

■ Pure white (RAL 9010)

# SiLine® Snack und Combi M RO

### **Basis**



- White aluminum (RAL 9006)
- Jet black (RAL 9005)

### Optional:

The standard design VA can be added with the design package A or B. Design RA can be complemented with Design package A.

### Design package A includes:

■ LED-Decoration strips above and below the glass panel

### Design package B includes:

- LED-Decoration strips above and below the glass panel
- Upper door decoration panel in stainless steel
- Kickplate in stainless steel

All design variants can be found in the brochure.

### **Options and accessories**

- Anti-vandalism panel
- Rain shield and weatherproof protection
- Coin insert slide and coin return drum
- Reinforced locking lever protection
- Security frame with side lock
- Laminated safety glass panel with UV filter
- Residual current circuit breaker
- High performance chiller unit with heater with "frost monitoring function", so that the internal temperature is held above 0°C
- Rear panel offers advertising opportunity

### Optional

- Lift
- Impact protection made of 8 mm thick laminated safety glass instead of 12mm PC
- KESO



Sielaff GmbH & Co. KG Automatenbau Herrieden Münchener Str. 20 91567 Herrieden Germany

Phone: +49 9825 18-0 Telefax: +49 9825 18-311155

info@sielaff.de www.sielaff.com See here for our company profile video



